




60064 | whitewash elegant oak

AUSTRALIAN STOCKED LUXURY VINYL TILE

allura® flex II

Allura Flex II is a collection of high-quality, dimensionally stable heterogeneous modular vinyl tiles and planks, perfect for multi-level buildings and commercial applications. The new Flex is engineered with a double glass reinforcement for leading dimensional stability yet is easy to cut and install.

ACOUSTIC COMFORT



- Can be installed alongside our Tessera and Flotex planks & tiles without the need for transition strips.
- The stable yet flexible solution for demanding applications of any size.
- Surpasses the NCC requirements for impact sound reduction, often eliminating the need for underlay.



60350 | white autumn oak

To order a sample or check stock levels, please contact your local Forbo representative, order online at www.forbo-flooring.com.au/alluraflex or call Customer Service on **1800 224 471**.

creating better environments

Forbo

FLOORING SYSTEMS

allura® flex^{ll} FL5

0.55 mm wear layer



Combining realistic visuals with acoustic performance.

Allura Flex^{ll} 0.55 LVT offers true-to-life wood and stone patterns, as well as delivering acoustic performance and impressive durability.



bleached timber
63406FL5
120 x 20 cm | ↕ ⊕



blond timber
63412FL5
120 x 20 cm | ↕ ⊕



natural timber
63535FL5
120 x 20 cm | ↕ ⊕



63535 | natural timber



charcoal concrete
62418FL5
50 x 50 cm


natural colour
variation


in register
embossing


2 or 4 sides
bevelled

		Flex ^{ll} 1.00	Flex ^{ll} 0.55
Total thickness	EN-ISO 24346	5 mm	4 mm
Wear layer thickness	EN-ISO 24340	1 mm	0.55 mm
Domestic use	EN-ISO 10874	Class 23	Class 23
Commercial use	EN-ISO 10874	Class 34	Class 33
Light industrial use	EN-ISO 10874	Class 42	Class 42
DoP		0200131-Dop_209	0200131-Dop_209
Reaction to fire	ISO 9239.1	CRF: >4.5kW/m ² Smoke: <750%.min	
Slip resistance	AS 4586:2013	R10	R10
Impact noise	ISO 717-2	14 dB*	13 dB*
Thermal conductivity	EN 12524	0.25 W/mK	0.25 W/mK
Environmental	GBCA GreenStar Rating System	GreenTag Level A; Best Practice PVC	

* L_{nT,w} acoustic test results are available upon request.
Our recommended adhesive is Forbo F34. Full technical specifications are available on at www.forbo-flooring.com.au.



white autumn oak
60350FL5
100 x 15 cm | ↕ ⊕



natural giant oak
60284FL5
150 x 28 cm | ↕



central oak
60300FL5
150 x 28 cm | ↕ ⊕



deep country oak
60302FL5
150 x 28 cm | ↕ ⊕



60300 | central oak



whitewash elegant oak
60064FL5
120 x 20 cm



waxed oak
60063FL5
100 x 15 cm | ↕



natural collage oak
60374FL5
120 x 20 cm | ↕

allura® flex^{||} FL1

1.0 mm wear layer



The ultimate heavy duty and acoustic comfort solution for commercial applications.

Allura Flex^{||} 1.0 is a LVT that offers high quality, dimensionally stable planks and tiles. With excellent acoustic performance, it is ideal for commercial applications with heavy traffic.



light honey oak
60305FL1
150 x 28 cm | ↕ ⊕



central oak
60300FL1
150 x 28 cm | ↕ ⊕



deep country oak
60302FL1
150 x 28 cm | ↕ ⊕



natural giant oak
60284FL1
150 x 28 cm | ↕



rustic anthracite oak
60306FL1
150 x 28 cm | ↕ ⊕



grigio concrete
62523FL1
50 x 50 cm



charcoal concrete
62418FL1
50 x 50 cm



To order a sample or check stock levels, please contact your local Forbo representative or order online at www.forbo-flooring.com.au/alluraflex or call Customer Service on **1800 224 471**.